





Leica DISTO™ Family



True originals: Our laser distance meters

Using a Leica Geosystems DISTO™ you can measure distances, areas, volumes, tilts and much more, anywhere. Quick, simple and completely spot-on without the help of another person. Saving you valuable time and unnecessary costs.

Proven Leica optics and Power Range Technology™ ensure the highest precision. You can measure distances up to 650 ft with pinpoint accuracy.

Even distances in difficult to reach places can be captured quickly and easily, in just a few seconds. No need for risky methods of working that could lead to accidents.





Leica DISTO™ D1 Part # 846805 Handy, simple, precise!

At the touch of a button the Leica DISTO™ D1 measures heights, distances as well as niches quickly and reliably.

- Bluetooth® Smart for data transfer to smart phones and tablets
- Free App Leica DISTO™ Plan
- 130′ range
- XRange Power Technology
- Clear, illuminated 3 line display



Leica DISTO™ D2 Part # 838725 Compact Device - Outstanding Range

Leica's solution to reduce time and costs.

Just press a button to measure distances, calculate square areas and volumes -fast, easy and precise.

- Longest range in class -up to 330'
- Accuracy: ± 1/16"
- Bluetooth® Smart
- Automatic end-piece detection
- Area, Volume, Wall-area, Perimeter
- Pythagoras, Stake-out, Last 10 measurement memory
- Large illuminated 3-line display
- Send data to your Smartphone or tablet

Free App Leica DISTO™ Plan







Bluetooth°

Leica DISTO™ D5 Part # 950908

Part # 950879 Pro kit

Strong in Outdoor Areas

The Leica DISTO™ D5 is particularly suitable for distance measurements in outdoor areas. Thanks to the digital Pointfinder, the high functionality and the compatibility with the Leica DISTO™ Plan app, every measuring situation is solved quickly and efficiently. The results can be easily documented to support a target-oriented and error-free digital workflow.

- Large 2.4" Scratch resistant screen for quick intuitive operation
- Measure with a picture
- Image Download via USB
- 650ft Range, ± 1/16" accuracy
- 0.1 degree accuracy tilt sensor for high accuracy vertical measurements
- Bluetooth 5.0 Smart (works with iOS and Windows hardware/software supporting Bluetooth 5.0 Smart Ready)









Free App - Leica DISTO™ Plan*

Measurement data can be transferred using the Bluetooth® Smart Technology. The free app Leica DISTO™ Plan supports the creation of ground plans or tables on iPhone, iPad and Android supporting BT 4.0. Dimensions can also be entered onto photographs.



197.992_m

DISTO™ D5







Leica DISTO™ X3 Part # 850834

Rugged design for tough conditions

- Water jet and dust protected to IP 65 standards
- 2m drop tested
- Solid rubber housing
- End-piece XL
- Bluetooth® Smart document and visualise
- Stake-out a well known function re-invented
- Create sketches, plans an document your measurements on your smartphone or tablet automatically when taking measurements





New App - Leica DISTO™ Plan

New Leica DISTO $^{\text{TM}}$ technologies in combination with the Smart Room function of the Leica DISTO $^{\text{TM}}$ Plan app allow you to quickly create scaled floor plans on your smartphone or tablet.



Leica DST 360 Part # 848783

The Leica DST 360 transforms your DISTO™ X3 or X4 and-held laser device into a measurement station. It allows you to measure distances between any two points from one

Leica DST 360-X Part # 946095

The Leica DST 360-X works with DISTO X6 to create point-to-point measuring.

Leica TRI 120 Tripod Part # 848788 In a carton box.





Leica DISTO™ E7100i Part # 812806

The first pocket-sized laser distance meter with Bluetooth®

The simple four-button interface puts distance measurement and area measurement at your fingertips. Hit the Bluetooth button to synch up the free Leica DISTO Plan App on a mobile device and capture measurements in real time as you take them. When your done, the app creates a PDF with your measurements laid over a diagram or a photo.

- Professional laser measurement tool with Bluetooth.
- Easily send accurate room measurements to your mobile device.
- Use the DISTO Plan App to create and share floorplans.
- Four button simplicity.



Free App - Leica DISTO™ Plan*

Measurement data can be transferred using the Bluetooth® Smart Technology. The free app Leica DISTO™ Plan supports the creation of ground plans or tables on iPhone, iPad and Android supporting BT 4.0. Dimensions can also be entered onto photographs.

Tech Data	Part #	Accuracy	Tilt	Range	Size	Weight	Protection	ISO Rating	Bluetooth
D1	846805	~ 1/16", ±1.5 mm		0.60" to 130'	4.5"×1.7" ×.92"	3.53 oz.	IP54	ISO 16331-1	4.0
D2	838725	~ 1/16", ±1.5 mm		1.97" to 328'	4.6"×1.7" ×1.02"	3.53 oz.	IP54	ISO 16331-1	4.0
D5	950908	~ 1/16", ±1 mm	360°	1.6" to 650'	5.67"×2.36" ×1"	6.4 oz.	IP54	ISO 16331-1	4.0
Х3	850834	~ 1/16", ±1 mm	360°	1.6" to 492'	5.2"x2.2" x 1.14"	6.49 oz.	IP65	ISO 16331-1	4.0
Х6	950909	~ 1/16", ±1 mm	360°	2" to 820'	6.1"x2.7" x 1"	8.1 oz.	IP65	ISO 16331-1	4.0
E7500i	792320	~ 1/16", ±1 mm	360°	1.6" to 660'	5.6" x 2.3" x 1.1"	7.00 oz	IP65	ISO 16331-1	4.0

^{*} In accordance with ISO 16331-1. See DISTO manual or Leica website for complete specifications.











Part # 950909 Part # 950878 P2P kit,

Efficient Measurement for Digital Workflows P2P Technology is a safe, accurate and efficient measurement method when it comes to distance measurements in inaccessible areas or complex measurement situations. It also enables a completely digital workflow, as the captured measurement results can be further processed in any CAD software.

- Measure the distance between any two points
- Measure any area by just measuring its corners
- New tripod adapter for precise aiming
- Create a CAD file right on your DISTO™
- Send point data right into your CAD system
- Bluetooth® Smart
- Range: up to 820'

Technical Data	Part #	Accuracy	Tilt	Range	Size	Weight	Protection	ISO Rating
X6	950909	1/16" 1 mm	360°	2" to 820'	6.1"×2.7" ×1"	8.1 oz.	IP65	ISO 16331-1



and angle measurements determine the precise position of each point targeted with the integral camera and captured with the laser beam. In short: the Leica 3D Disto detects the location and the height of the target point. ■ New software shows measurements in 3D ■ Measure from one station – every visible point can be measured by targeting with the visible laser dot -without

> the need to walk to the target ■ Measure to difficult-to-reach points, such as roof edges

■ As-built records of ceiling, floor and roof surfaces, volumes, inclination, falls, height differences, angles

Plumbing of points, parallel offsetting of axis, levelling, transferring levels from wall to wall. Forget spirit level and measuring tapes!

■ Realtime, 3D display of measurements on the tablet screen as a job is being measured

■ Positionally accurate representation of the measured points in the camera display

■ Data import and export on PC and USB stick

Technical Data	Part #	Accuracy	Tilt	Range	Size	Weight	Protection	ISO Rating
3D DISTO	844692	1/8" @ 100'	H 360° V 250°	1.65' to 165'	7.4" × 8.5"	6.2 lbs.	IP54	ISO 16331-1



Leica Lino Family



The accurate, self-levelling point and line lasers

With Leica Linos everything is plumb and perfectly aligned. Leica Linos project lines or points with absolute precision. The time-consuming and tedious techniques of drawing lines and marking points are things of the past.

- Self-levelling: Leica Linos automatically compensate for minor angular misalignments by levelling themselves over a range of $\pm 4^{\circ}$. So you can avoid errors.
- Proven optics: Top quality optics and proven Power Range Technology™ ensure that the projected laser lines and points are highly visible and accurate.
- Simple operation: With only two buttons, Leica Linos are simple and intuitive to use.
- Pendulum Lock



Leica Lino L4P1 pack Part # 834838 the most powerful multi line laser

The Leica Lino L4P1 is our latest and most powerful multi line laser, which supports efficient and quick workflows for dry wall installers, tilers and many other interior trades. Its innovative and unique power concept and its versatility makes it the first choice.

- Precision: 360° rotation base with fine
- Innovative Li-Ion power: 24 h battery life on a single charge
- Versatility: Only one device needed for all interior applications


Technical Data	P5	L2	L2P5	L2G	L2P5G	L6R	L6G	L4P1
Part #	864427	864413	864431	864420	864435	912969	912971	834838
Measuring range	98'	82'	82'	115'	115'	82'	115'	49'
Range with detector	N/A	262'	262'	262'	262'	210'	210'	262'
Levelling accuracy	± 0.002"/'	± 0.002"/'	± 0.002"/'	± 0.002"/'	± 0.002"/'	± 0.002"/'	± 0.002"/'	± 0.002"/'
Self-levelling range	± 4°	± 4°	± 4°	± 4°	± 4°	± 4°	± 4°	±3°
Number of points	5	N/A	4	N/A	4	N/A	N/A	1
Lines	N/A	2	2	2	2	3-360°	3-360°	4

One powerful new platform



Leica Lino P5 Part # 864427

The Leica Lino P5 point laser is very easy to use. At the push of a button, it accurately projects five reference points at exact right angles to one another.



Leica Lino L2 Part # 864413 (red laser technology) **Leica Lino L2G** Part # 864420 (green laser technology) The high-precision optics of the Leica Lino L2 and L2G ensure outstanding laser line visibility up to 82 feet, depending on lighting conditions. Its exceptionally long horizontal and vertical laser lines are projected to floors, walls and ceilings at more than 180 degrees.



Leica Lino L2P5 Part # 864431 (red laser technology) **Leica Lino L2P5G** Part # 864435 (green laser technology) The Leica Lino L2P5G uses the best green laser technology and combines it with the functionalities of a cross line laser and a point laser. Its green laser beams and points are up to four times more visible to the human eye compared to red ones, which makes it the ideal tool for bright environments and large rooms.



Leica Lino L6R Part # 912969

360° laser line projection for multi-directional alignment - perfect for indoor applications. The laser's vertical lines are easily adjusted once the plumb point, which is located outside the device, is set. This unique feature allows the plumb point (cross-section of two vertical lines) to stay in position while the two vertical lines rotate around it by ±10°.



Leica Lino L6G Part # 912971

360° green laser lines ensure highest visibility of up to 210 feet in diameter; making this the perfect tool for multi-directional alignment, plumbing, levelling and squaring tasks in large and bright environments.

NEW Leica Lino Accessories









Leica NA300/500/700 Series

Automatic Levels - Reliable levels for your site







- Quick and easy measurements
- Unique design and highest quality of results for levelling needs
- Manufactured for the most rugged sites and the harshest conditions
- Protected shape for increased ergonomic handling while ensuring the highest quality results
- Simple handling for quick and accurate measurements
- Distinctive design and proven technology, inside and out

Technical data	NA320/324/332	NA520/524/532	NA720/724/730 plus
Magnification	20×, 24x, 32x	20×, 24x, 32x	20×, 24x, 30x
Standard deviation (per 1 km double levelling)	.098", .079", .071"	.098", .075", .063"	.098", .079", .059", .047", .028"
Measuring angle	360°	360°	360°
Spray proof / dust protected	IP54	IP54	IP57

Leica Piper 100/100G/200/200G

The world's most versatile red or green pipe laser

Built with a rugged aluminum housing, these pipe lasers perform powerfully even in tough jobsite conditions. The Leica Piper is the only pipe laser that fits inside a 4 inch pipe.

And there is more... The Piper Green Series comes with 4 times better laser visibility for longer working distances while achieving higher accuracy while remaining the smallest pipe laser in the market.

- Grade checking in all gravity flow pipe
- Gravity flow pipe lining
- Sanitary sewers
- Storm sewers
- Culverts



Technical Data	Working Range	Grade Range	Self leveling Range	Size	Weight	Protection	Battery Life
100/100G/200/200G	up to 650'	-10% to +25%	-15% to +30%	3.8" Dia.	4.4 lbs	IP68	40 hours

Leica Rugby 600 Series

Your reliable team player on site

Leica Rugby lasers are the toughest rotating lasers suitable for all construction applications. Level, align and square much quicker than ever before, eliminating costly errors and downtime.

- Simple and reliable
- Choice of Alkaline or Li-Ion batteries
- 3-year warranty, Rugby 680 5-year warranty
- Protection class IP67











		-			
Technical Data	Rugby 610	Rugby 620	Rugby 640	Rugby 640G	Rugby 680
Product type	General const.	General const.	Multipurpose/H.V.	Multipurpose/H.V.	Semi-auto grade
Laser class	Class 1	Class 1	Class 2	Class 2	Class 1
Functionality	Self-leveling horizontal, one button laser	Self-leveling horizontal & manual slope in one axis	Self-leveling horiz. & vert. 90° and manual slope in dual axis	Self-leveling horiz. & vert. 90° and manual slope in dual axis	Self -leveling horiz. dial-in grade in dual axis
Accuracy	± 3/32" @ 100'	± 1/16" @ 100'	± 1/16" @ 100'	± 1/16" @ 100'	± 1/16" @ 100'
Grade range	-	-	-	-	± 8% DG
Smart slope	-	-	-	-	Yes
Rotation - RPS	10	10	0, 2, 5, 10	0, 2, 5, 10	10
Range dia. RE 120	1,650'	2,000'	1,650'	1,650'	2,000'
Danga dia DE1/0/160	2.6001	2.6001	2 6001	2 6001	2.6001

Rugby 600 models are available with 3 receiver







Technical Data	Rod Eye 120 Basic	Rod Eye 140 Classic	Rod Eye 160 Digital
Detection window	3"	5"	5"
Detectable spectrum	600nm to 800nm	600nm to 800nm	600nm to 800nm
Numeric readout height	-	-	3.5"
Detection accuracies			
Very fine	-	-	± 0.02"
Fine	± 0.04"	± 0.04"	± 0.04"
Medium	-	± 0.08"	± 0.08"
Coarse	± 0.12"	± 0.12"	± 0.12"
Very coarse			± 0.20"

Leica Locators

Leica DD100 Series Locators

The Leica DD100 series locators reduce the complexity normally associated with locating of buried utilities. The DD100 series automated pinpointing process improves the detection of utilities, reduces utility damage and increases workforce safety

Leica DD SMART Utility Locators

The Leica DD SMART utility locators and DX Shield software open the door to a connected world, anywhere, anytime. Leica DD SMART utility locators detect underground assets deeper, faster and more accurately. The DD SMART utility locators are scalable and designed with onboard memory, GPS and Bluetooth technology. Connect and download data stored in the DD SMART utility locators' internal memory, including GPS positioning and transfer it back to the DX Shield software for analysis.



Leica DD120

For construction professionals who need to understand what is beneath their sites.

Leica DD130

For construction professionals who need to accurately locate and trace buried utilities.



Easy to use SMART utility locator, simplifying the detection of buried utilities.



Intuitive SMART utility locator combines enhanced trace capabilities with greater detection accuracy.

Technical Data DD120		DD130	DD220	DD230		
Frequency / Mode	Power mode 50 Hz or 60 Hz, Radio mode 15 kHz to 60 kHz, Transmitter mode 8 kHz a 33 kHz, Auto mode = Power + Radio mode					
Depth Range	Line: 1' - 10' Sonde: 1' - 10'	Line: 1' - 10' Sonde: 1' - 32.7'	Line: 4" - 16.4' Sonde: 4" - 23'	Line: 4" - 23' Sonde: 4" - 32.8'		
Protection	Conform	is to IP54	Conforms to IP66			
Battery life	15 h	iours	20 hours			
Depth accuracy	10%	10%	5%	5%		
Bluetooth® GPS & GIS	Not available	Not available	enabled	enabled		
Memory size	Not available	Not available	8 GB memory	8 GB memory		

Leica Detection and Mapping

A utility map shows the positioning and identification of buried pipes and cables beneath the ground. Combine mapping process with a topographical survey and the results will provide you with a comprehensive detailed map of utilities.



Leica DSX

Quickly and easily avoid, locate and map underground utilities with the new Leica DSX ground penetrating radar (GPR) solution. Unlike other GPR solutions, users do not require expertise in interpreting raw radar data. The DSX uses a smart algorithm in DXplore software to accurately field generate 3D utility maps on the tablet within minutes. No more waiting days for post processing! Optional integration of GPS/GNSS for mapping, with easily exported data in PDF and DXF formats. Additional integration with Leica MC1 machine control software aids excavating contractors in avoiding utility strikes using real time avoidance signals aboard excavators outfitted with Leica machine control systems.





The Leica DS2000 is a dual frequency utility detection radar which finds all potential utilities, both deep and shallow, including non-conductive pipes and fibre optics. Easily collect, store and export data for additional post processing in the office. The perfect system for users with previous experience using ground penetrating radar (GPR).



Portable Scanning

Reveal true data, make decisions now.



IDS C-Thrue Concrete Scanner

C-thrue all-in-one Ground Penetrating Radar (GPR)

C-thrue is an all-in-one Ground Penetrating Radar (GPR) for accurate scanning and real time analysis of concrete structures. Construction and service companies as well as civil and structural engineers can now improve the way they locate rebars, voids, post-tension cables, cavities, conduits, and any other objects buried in the structure before cutting or drilling into the concrete.

Features and Benefits:

Clearer and faster surveys

Detection of both first and second levels of rebars thanks to the system's double polarisation.

Safe drill in the surveyed structure

Rebar/void automatic insight capabilities that improve safety before cutting or drilling into the concrete.

Fully visible, multi-touch display

Data displayed on the screen are never obscured by the handle or the user's hand.

Simplified data interpretation

Optimal decision-making supported by visualization of acquired data in 3D models.

Increased data accuracy

Eliminate manual, error-prone paper grids with an automatic positioning and navigation system.

Advanced data visualization

Augmented reality for 3D data visualization and sharing across operators – in real time or intervals after acquisition.

Automated data acquisition and analysis

Automatic detection of the first layer of rebars and result exportation.



Accessories









Portable Hand Held Scanning

DUAL POLARISATION

Detection of both first and deeper levels.



New!

C-thrue XS


The compact hand-sized GPR with dual polarization to never miss a detail in one scan



C-thrue XS is the compact dual polarized GPR system for concrete inspection: the smallest and lightest antenna on the market capable of detecting shallow and deep targets in one scan. C-thrue XS, adding to the C-thrue product family, allows the most accurate scanning performance and real-time analysis of concrete structures with a hand-sized device able to perform in-depth inspections.



Standard view



C-thru XS Dual Antenna

DUAL ANTENNA POLARIZATION: DETECT SHALLOW AND DEEPER TARGETS IN A SINGLE MOVE.

Concrete inspection is fast and simple with the most accurate scanning performance to easily locate and identify rebars, ducts, cables and other objects.

Multiple configurations:

STANDALONE: Easily scan across any concrete inspection scenario with C-thrue XS and promptly visualize the collected data results on your tablet

INTEGRATED USE WITH C-THRUE: C-thrue

XS' combined use with C-thrue allows to cover any jobsite challenge and quickly visualize data on C-thrue's multi-touch display.

Real-time investigation of concrete structures is fast and simple with C-thrue XS. Its compact size and light weight allow to easily investigate hard to reach areas and around obstructions



All-in-one and One-for all Ground Penetrating Radar



New! Chaser XR


Extending the power of EsT technology to geophysical surveying

Chaser XR is the new powerful GPR solution setting a new standard in subsurface investigation. Expanding the power of EsT technology to geophysical surveying, Chaser XR is the all-in-one and one-for-all GPR antenna featuring the most extended inspection range on the market (80 MHz - 1500 MHz).

EsT | Equalized scrambled Technology: a next level performance in subsurface profiling.

Thanks to EsT, Chaser XR is able to offer unparalleled GPR performance maximizing subsurface profiling to a deeper range compared to any other solution available on the market.

This technology is able to exploit the entire radiating per-formance of the antenna for full control of the GPR signal, performing the best noise rejection and capturing both the lower and higher frequencies for an extended depth range and an ultra-high resolution.







One solution for multiple scenarios: Chaser XR's extended inspection range covers different geophysical surveying applications ranging from environmental assessment to tunnel inspection.


Organize and share your GPR data results for a comprehensive analysis of concrete inspections




New!


NDT Reveal


The professional CAD-based GPR software for Construction and Building inspections



NDT Reveal is the professional desktop GPR software for post-processing and analysis of data collected by C-thrue and C-thrue XS concrete inspection devices. NDT Reveal allows you to successfully organize and share your GPR data whilst streamlining your workflow in data processing and analysis. Enjoy accurate and comprehensive overviews on GPR data with easy integration of on-field inspection activities into the big picture of Building and Construction projects.







NDT REVEAL MAIN FEATURES

- Locate GPR jobsite surveys on the CAD drawing
- Display 2D and 3D GPR data and insert features (e.g. rebars, post tension cable voids and drill areas)
- Produce digital exports: DXF and DWG format
- Job site reports with 2D and 3D GPR data of detected items, photos, sketches and CSV tables.

NDT REVEAL BENEFITS

- Accurate overview on your Building and Construction projects
- Integrated visualization of data, photos, sketches
- Easy-to-create and complete jobsite reports

Recommended original accessories

Always perfectly equipped for your application

Leica Geosystems offers a comprehensive selection of accessories which you can use to adapt your laser distance meters and levels ergonomically to suit your respective task.



DA175 Signal Transmitter 1 watt (Part # 949370) when connected to a utility with output frequencies of 512Hz, 640Hz, 8kHz, 33kHz.

DA230 Signal Transmitter 1 watt (Part # 850274) or 3 watts (Part # 850275) when connected to a utility with output frequencies of 512Hz. 640Hz. 8kHz. 33kHz. 131kHz

Trace Rod 165' (Part # 850278) or 263' (Part # 850279) enables the complete a length of non-conductive drains, duct or pipe to be traced when used in conjunction with a DA series transmitters.

Transmitter Clamp 4" (Part # 850280) or 3.15" (Part # 850281) clamp, used in conjunction with the DA series transmitters and Locator to trace the route of buried utilities such as Telecom cable, Power cables and pipes.

Sondes - used to trace drains, sewers and other non-conductive utilities (part #s 850288, 850289, 850290, 850291, 856131



Tri70 Flat-head Tripod Part # 794963

The small and handy tripod for everyday use. Stable and turnable headplate with 1/4 - 20 threads. Perfect for the LINO series or in conjunction with the TA360, FTA360, FTA360S and your DISTO.

Tri100 Articulating-head Tripod Part # 757938
High quality tripod with 1/4-20 thread mounting plate and articulating elevator head for height adjustments. For use with Leica Disto models that incorporate a tripod mounting thread

Tri200 Flat-head Tripod Part # 828426

The TRI 200 is a surveyor style tripod that is more stable and durable than the standard issue TRI70. This package is for professionals that frequently measure on uneven grade, in rugged environments and in the elements.

CTP104 Aluminium tripod Part # 767710 Light tripod with shoulder strap and side clamp screws for Leica Jogger 20/24, Sprinter 50, Roteo and Rugby

CTP104D-1 Dome-head tripod Part # 790226 Dome-head light tripod with shoulder strap and side clamp screws. 5/8 x 11 fixing screw with hook for plumb bob



GZM3 Target plate

Part # 820943

For 3D DISTO™ and DISTO™ S910

GZM26 Target plate, DIN A4

Part # 723385

8.25"~x~11.5", white side for shorter distances, brown side for longer distances, for all Leica DISTOs $^{\text{TM}}$

GZM27 Target plate set

Part # 723774

5.75" x 3.85" stick-on with kneading adhesive, for all Leica DISTOs $^{\text{TM}}$

GZM30 Target plate set

Part # 766560

7.75" x 10.75" for setting-up on floor marks, for all Leica DISTOs $^{\text{TM}}$

More practical accessories

LSA360-S Adapter

Red Laser glasses Part # 780117

Red laser glasses for improved visibility of red lasers

LSA360-S Adapter

Part # 838704

Designed specifically for the S910, D810 touch, D510, D410. The adapter mounts to a typical survey range pole with diameters from 0.45" - 1.35").

TSA360-S Adapter

Part # 828414

High precision tripod adapter for the Leica DISTO™ S910

LINO wall mount bracket

Part # 758839

Universal application thanks to screw fixing (1/4" screw)

TA360 Tripod Adapter

Part # 778359

Allows the base of the disto to remain in a fixed position for accurate calculation. Use with Tri70 tripod.

For DISTO™ E7400x, D330i, D5, D8

FTA360 Tripod Adapter

Part # 799301

Tripod adapter with fine-adjustment for easy and precise targeting. Use with Tri70 and Tri100 tripods. For DISTO™ D810, E7500 and E7500i

FTA360-S Tripod Adapter

Part # 828414

Tripod adapter with fine-adjustment for easy and precise targeting. Use with Tri70 and Tri100 tripods.
For DISTO™ S910 only

USB Battery charger for DISTO™ D810 & S910

Part # 806566

Plug into the cigarette lighter and charge your Leica DISTO™ D810 touch



TSA360-S Adapter

LINO wall mount

TA360 Tripod Adapter

bracket

FTA360 Tripod Adapter

Worldwide service and support

Leica Geosystems are pioneers in laser precision for measuring technology and guarantee quality and reliability. All our products have the benefit of our worldwide network of service centers and dealerships. Leica Geosystems is always somewhere close to you.



Dealer Information:

Leica Geosystems

5051 Peachtree Corners Circle Suite 250 Norcross, GA 30092 USA

www.leica-geosystems.us www.DISTO.com

Part No. 8237944

