



# Leica Zeno FLX100 plus Smart Antenna Data sheet



Location data is a commodity that underpins decision making no matter the industry.

The Leica Zeno FLX100 plus smart antenna captures spatial data in a simple and flexible way allowing you the freedom to work how you want.

A universal handheld tray enables you to pair the FLX100 plus with your own smartphone or tablet. For higher accuracy data capture just use a survey pole leveraging HxGN SmartNet RTK technology.

Use Leica Zeno Mobile for the ultimate experience in professional data capture or pair with Leica Zeno Connect to enable high accuracy positioning in other data collection apps on various operating systems.

**Leica FLX100 plus is your flexible solution from a trusted partner.**

#### LEICA ZENO FLX100 plus SMART ANTENNA:

- **GIS data collection made easy:** Simplify your workflows and unfold new ways of working.
- **Centimetre accuracy compact GNSS:** Real multifrequency tracking with 2 cm horizontal (2D) accuracy in an ultra-portable housing.
- **Build your GIS handheld solution:** Pair the FLX100 plus with the universal handheld tray and your mobile device to create the handheld solution that fits your needs.
- **Use any Android, iOS or Windows mobile device:** The FLX100 plus is compatible with all major operating systems.
- **Use Zeno Mobile or any other data collection app:** Combine with Zeno Mobile or your selected 3rd party software to maintain existing workflows.
- **Rugged, made for tough worksites:** Be ready to face the toughest conditions. The FLX100 plus is protected against water, dust and drops from 1.2 meters.
- **Leica Geosystems support and service:** Benefit from 2 years of warranty and Leica's professional service and support.

[leica-geosystems.com](http://leica-geosystems.com)



- when it has to be **right**

**Leica**  
Geosystems



# Leica Zeno FLX100 plus Smart Antenna

## GNSS TECHNOLOGY

Horizontal real-time accuracy	RTK (Multi-frequency): 2 cm + 1 ppm* SBAS (L1 only): <0.9 m* Navigated: 1.2 m*
Vertical real-time accuracy	RTK (Multi-frequency): 3 cm + 1 ppm*
Post-processing accuracy static mode	Horizontal: 2 cm + 1 ppm* Vertical: 3 cm + 1 ppm*
Satellite signal tracking	<ul style="list-style-type: none"> <li>■ GPS (L1 C/A, L2C)</li> <li>■ Glonass (L10F, L20F)</li> <li>■ BeiDou (B1I, B2I)</li> <li>■ Galileo (E1B/C, E5b)</li> <li>■ QZSS (L1C/A, L2C)</li> <li>■ SBAS: WAAS, EGNOS, MSAS, GAGAN (L1 C/A)</li> </ul>
Number of channels	184 channels
Update rate	Up to 10 Hz (0.10 sec)
Supported operating systems	<ul style="list-style-type: none"> <li>■ Android</li> <li>■ iOS</li> <li>■ Windows</li> </ul>
Real-time protocols	RTCM 3.0, RTCM 3.1, RTCM 3.2, RTCM 3.3, RTCM MSM
GNSS initialization	<ul style="list-style-type: none"> <li>■ Cold Start: 24 sec</li> <li>■ Reacquisition: 2 sec</li> </ul>
User interface	On/Off key status indicator (LED): satellite tracking, corrections, Bluetooth® communication and battery power
Communication port	Bluetooth® 5.0

## POWER MANAGEMENT

Battery	Internal (3.8 V / 6120 mAh)
Battery charging time	4 hours to full charge
Power	DC 5V/2A
Operating time	>20 hours
<b>PHYSICAL SPECIFICATIONS</b>	
Weight and dimensions	319 g, 139 mm x 80.6 mm x 31 mm
Proof against water, sand and dust	IP67
Operating/Storage temperature range	<ul style="list-style-type: none"> <li>■ Operating: -40 to 65 °C</li> <li>■ Storage: -40 to 80 °C</li> </ul>
Humidity	Rarely and slightly condensing. ISO 9022-12-04 (+65 °C, 92 %, 62 h)
Drop	1.2 m
Vibration	Withstands strong vibration. ISO 9022-36-05 (10-55 Hz / ±0.15 mm / 5 cycles)



GG04 PLUS SMART ANTENNA



LEICA ZENO TAB 2



ZENO MOBILE

Survey grade GNSS receiver. RTK, Multi-constellation, Multi-frequency 1cm + 1ppm Multipath mitigation	Android 8.0	Intuitive feature editing and attribute entry
GPS, GLONASS, Galileo, BeiDou, QZSS, SBAS	8" sunlight readable screen (1280 x 800)	Professional multi-collect and stakeout tools available
iOS, Android and Windows support	IP67 & 1.2 m drop resistant, MIL-STD-810G, MIL-STD-461F	Create and connect to RTK sources
Precise Point Positioning (PPP) for cm level accuracy without Internet connection	GSM, Wi-Fi, Bluetooth®, NFC	Comprehensive coordinate system support and configuration



ArcGIS System Ready  
Specialty

The Bluetooth® word mark and logos are owned by Bluetooth SIG, Inc. and any use of such marks by Leica Geosystems AG is under license.

Microsoft, Windows® and the Windows logo are either registered trademarks or trademarks of Microsoft Corporation in the United States and / or other countries. Other trademark and trade names are those of their respective owners.

Apple, iPad, iPad Air, iPad Pro, and iPhone are trademarks of Apple Inc., registered in the U.S. and other countries.

Android™ is a trademark of Google Inc.

iOS is a trademark or registered trademark of Cisco in the U.S. and other countries and is used under license.

Use of the Made for Apple badge means that an accessory has been designed to connect specifically to the Apple product(s) identified in the badge, and has been certified by the developer to meet Apple performance standards. Apple is not responsible for the operation of this device or its compliance with safety and regulatory standards.

Support of different iOS and Android versions cannot be guaranteed at all times as operating system updates are out of Leica Geosystems control. Leica Geosystems publishes a list of fully tested and verified operating system versions on the customer information portal myWorld.

\* Measurement precision under good to favourable conditions. Accuracy and reliability depend upon various factors including number of available satellites, geometry, proximity to base station, multipath effects, ionospheric conditions, etc

Copyright Leica Geosystems AG, 9435 Heerbrugg, Switzerland. All rights reserved. Printed in Switzerland - 2020 Leica Geosystems AG is part of Hexagon AB. 971467 en - 06.22

**Leica Geosystems AG**  
Heinrich-Wild-Strasse  
9435 Heerbrugg, Switzerland  
+41 71 727 31 31

- when it has to be **right**

**Leica**  
Geosystems